



Geschweißt-gezogene Präzisionsstahlrohre nach EN 10305-2 (DIN 2393)

Cold Drawn Welded Precision Steel Tubes acc. to EN 10305-2 (DIN 2393)

Stand: 2014-02 V 1.00

		Wanddicke (T) / Wall Thickness (WT) **																		
mm		0,800 0,890 1,000 1,200 1,240 1,500 1,650 1,750 1,800 2,000 2,180 2,200 2,410 2,500 2,790 2,800 3,000 3,180 3,430																		
inch		0,031 0,035 0,039 0,047 0,049 0,059 0,065 0,069 0,071 0,079 0,086 0,087 0,095 0,098 0,110 0,110 0,118 0,125 0,135																		
Nennmaß Nominal Size	zul. Ab- weichung Tolerance	Nennmaß Nominal Size	zul. Ab- weichung Tolerance																	
10,00	± 0,08	0,394	± 0,003																	
12,00		0,472																		
12,70		0,500																		
14,00		0,551																		
15,00		0,591																		
15,88		0,625																		
16,00		0,630																		
18,00		0,709																		
19,05		0,750																		
20,00		0,787																		
22,00		0,866																		
22,23		0,875																		
23,00		0,906																		
24,00		0,945																		
25,00		0,984																		
25,40		1,000																		
26,00		1,024																		
28,00		1,102																		
28,58		1,125																		
30,00		1,181																		
31,75	± 0,15	1,250	± 0,006																	
32,00		1,260																		
33,00		1,299																		
34,00		1,339																		
34,93		1,375																		
35,00		1,378																		
38,00		1,496																		
38,10		1,500																		
40,00		1,575																		
41,28	± 0,20	1,625	± 0,008																	
42,00		1,654																		
44,45		1,750																		
45,00		1,772																		
46,00		1,811																		
47,63		1,875																		
48,00		1,890																		
49,00		1,929																		
50,00		1,969																		
50,80	± 0,25	2,000	± 0,010																	
51,00		2,008																		
52,00		2,047																		
53,96		2,124																		
55,00		2,165																		
56,00		2,205																		
57,15		2,250																		
60,00		2,362																		
60,03	± 0,30	2,363	± 0,012																	
63,50		2,500																		
65,00		2,559																		
69,85		2,750																		
70,00		2,756																		
73,00	± 0,35	2,874	± 0,014																	
75,00		2,953																		
76,20		3,000																		
80,00		3,150																		
82,55	± 0,40	3,250	± 0,016																	
85,00		3,346																		
88,90		3,500																		
90,00		3,543																		
95,00	± 0,45	3,740	± 0,018																	
95,25		3,750																		
100,00		3,937																		
110,00	± 0,50	4,331	± 0,020																	
120,00		4,724																		

Außendurchmesser (D) / Outside Diameter (OD) \*\*

Weitere Abmessungen und \*\* Toleranzen auf Anfrage / Other dimensions and \*\* tolerances on request

=Standard Lieferprogramm / Standard Product Range  
 =Kunden Lieferprogramm / Costumer Product Range